

不锈钢内螺纹截止阀

Stainless steel Inside screw Globe Valve



上慧阀门

www.shxvalve.com

截止阀系列

特点:

全通径流量

产品规格从1/2"到2"

工作压力:200PSI

内螺纹端可按BSPT、NPT、DIN2999制造


Feature

Full Bore

Size: 1/2" to 2"

Working Pressure: 200PSI

Female Threaded End: BSPT, NPT, DIN2999



材料列表 Materiallist

| No | 部件名称 Part Name | 材料 Material | |
|----|---------------------|-------------|-------|
| 1 | 阀体 Body | CF8M | CF8 |
| 2 | 阀瓣 Disc | CF8M | CF8 |
| 3 | 密封圈 Seal Ring | SS316 | SS316 |
| 4 | 阀杆 Stem | SS316 | SS304 |
| 5 | 填料 PTFE | PTFE | |
| 6 | 手轮 Handwheel | HT(C.R.) | |
| 7 | 阀盖 Bonnet | CF8M | CF8 |
| 8 | 压盖螺母 Gland Nut | SS316 | |
| 9 | 填料压盖 Packing Gasket | SS316 | |
| 10 | 螺母 Nut | SS316 | |

尺寸列表 Dimension List

单位:Unit:mm

| NPS | d | H | L | W |
|--------|----|-----|----|-----|
| 1/2" | 15 | 105 | 50 | 70 |
| 3/4" | 20 | 108 | 60 | 70 |
| 1" | 25 | 135 | 65 | 80 |
| 1-1/4" | 32 | 145 | 75 | 80 |
| 1-1/2" | 40 | 155 | 85 | 90 |
| 2" | 50 | 185 | 95 | 100 |