



电动截止阀

Electric Globe valves J41W/Y-16P/R/I



上慧阀门

www.shxvalve.com



主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

公称口径 DN	主要外形尺寸和连接尺寸 (mm) Main external and connecting dimensions									WT(Kg)
	L	D	D1	D2	b	f	Z-d	H	D0	
J41 ^H _B -16C J41W-16P J41W-16R J41Y-16I										
10	130	90	60	40	14	2	4-14	198	120	4.7
15	130	95	65	45	16	2	4-14	218	120	5.2
20	150	105	75	55	16	2	4-14	258	140	7.1
25	160	115	85	65	16	2	4-14	275	160	7.4
32	180	135	100	78	18	2	4-18	280	180	8.5
40	200	145	110	85	18	3	4-18	330	200	12.5
50	230	160	125	100	18	3	4-18	350	240	20
65	290	180	145	120	18	3	4-18	400	280	25
80	310	195	160	135	20	3	8-18	355	280	35
100	350	215	180	155	22	3	8-18	415	320	50
125	400	245	210	185	24	3	8-18	460	360	75
150	480	280	240	210	24	3	8-23	510	400	100
200	600	335	295	265	26	3	12-23	710	400	210
250	650	405	355	320	30	3	12-23	768	450	446
300	750	460	410	375	30	3	12-23	925	500	648



主要外形和连接尺寸 Main External and Connection Dimension

公称 通径 DN	主要外形尺寸和连接尺寸 (mm) Main external and connecting dimensions										电动装置 Electric device		WT(Kg)	
	L	D	D1	D2	b	f	Z-d	H手	H电	D0	手动 Hand	电动 Electric		
J41 $\frac{H}{Y}$ -25 J41W-25P J41W-25R J41Y-25I J941 $\frac{H}{Y}$ -25 J941W-25P J941W-25R J941Y-251I														
10	130	90	60	40	16	2	4-14	198	-	120	-	4.9	-	
15	130	95	65	45	16	2	4-14	218	-	120	-	5.4	-	
20	150	105	75	55	16	2	4-14	258	-	140	-	7	-	
25	160	115	85	65	16	2	4-14	275	-	160	-	7.4	-	
32	180	135	100	78	18	2	4-18	280	-	180	-	8.5	-	
40	200	145	110	85	18	3	4-18	330	-	200	-	12.5	-	
50	230	160	125	100	20	3	4-18	350	645	240	DZW101	16	50	
65	290	180	145	120	22	3	8-18	400	690	280	DZW101	25	62	
80	310	195	160	135	22	3	8-18	355	715	280	DZW151	30	67	
100	350	230	190	160	24	3	8-23	415	770	320	DZW20	34.5	73	
125	400	270	220	188	28	3	8-25	460	780	360	DZW30	89	127	
150	480	300	250	218	30	3	8-25	510	875	400	DZW45	98	215	
200	600	360	310	278	34	3	12-25	710	967	400	DZW60	180	322	
250	650	425	370	332	36	3	12-30	786	-	450	-	446	-	
300	750	485	430	390	40	4	12-30	925	-	500	-	654	-	

公称 通径 DN	主要外形尺寸和连接尺寸 (mm) Main external and connecting dimensions												电动装置 Electric device		WT(Kg)	
	L	D	D1	D2	D6	b	f	f2	Z-d	H手	H电	D0	手动 Hand	电动 Electric		
J41 $\frac{H}{Y}$ -40 J41W-40P J41W-40R J41Y-40I J941 $\frac{H}{Y}$ -40 J941W-40P J941W-40R J941Y-40I																
10	130	90	60	40	35	16	2	4	4-14	198	-	120	-	4.9	-	
15	130	95	65	45	40	16	2	4	4-14	233	-	120	-	5.4	-	
20	150	105	75	55	51	16	2	4	4-14	275	-	140	-	7	-	
25	160	115	85	65	58	16	2	4	4-14	285	-	160	-	8.8	-	
32	180	135	100	78	66	18	2	4	4-18	302	-	180	-	11.8	-	
40	200	145	110	85	76	18	3	4	4-18	355	-	200	-	16.5	-	
50	230	160	125	100	88	20	3	4	4-18	373	645	240	DZW101	24	61	
65	290	180	145	120	110	22	3	4	8-18	408	690	280	DZW101	33	75	
80	310	195	160	135	121	22	3	4	8-18	436	715	320	DZW201	44	84	
100	350	230	190	160	150	24	3	4.5	8-23	480	770	360	DZW301	60	101	
125	400	270	220	188	176	28	3	4.5	8-25	558	782	400	DZW45	89	207	
150	480	300	250	218	204	30	3	4.5	8-25	611	875	400	DZW60	98	226	
200	600	375	320	282	260	38	3	4.5	12-30	720	1160	400	DZW901	190	339	

电动截止阀

Electric Globe valves J41/Y-64 W/Y-64-160/1



上慧阀门
www.shixuevalve.com

截止阀系列

主要外形和连接尺寸 Main External and Connection Dimension

公称 口径 DN	主要外形尺寸和连接尺寸 (mm) Main external and connecting dimensions												电动装置 Electric device		WT(Kg)	
	L	D	D1	D2	D6	b	f	f ₂	Z-d	H手	H电	D0	手动 Hand	电动 Electric		
J41 ^H _Y -64 J941 ^H _Y -64 J41Y-64I J941Y-64I																
10	170	100	70	50	35	18	2	4	4-14	198	-	120	-	5.7	-	
15	170	105	75	55	41	18	2	4	4-14	195	-	140	-	10	-	
20	190	125	90	68	51	20	2	4	4-18	228	-	160	-	13	-	
25	210	135	100	78	58	22	2	4	4-18	275	-	180	-	14.5	-	
32	230	150	110	82	66	24	2	4	4-23	325	-	200	-	19	-	
40	260	165	125	95	76	24	3	4	4-23	360	-	240	-	25	-	
50	300	175	135	105	88	26	3	4	8-23	410	710	280	DZW10	35	64	
65	340	200	160	130	110	28	3	4	8-23	450	750	320	DZW15	48	77	
80	380	210	170	140	121	30	3	4	8-23	485	785	360	DZW30	56	88	
100	430	250	200	168	150	32	3	4	8-25	537	837	400	DZW45	125	171	
125	500	295	240	202	176	26	3	4	8-30	631	-	400	-	131	-	
150	550	340	280	240	204	38	3	4	8-34	646	-	450	-	157	-	
200	650	405	345	300	260	44	3	4	12-34	813	-	500	-	283	-	
J41 ^H _Y -100 J941 ^H _Y -100 J41Y-100I J941Y-100I																
10	170	100	70	50	35	20	2	4	4-14	198	-	120	-	6	-	
15	170	105	75	55	40	20	2	4	4-14	202	-	140	-	11	-	
20	190	125	90	68	51	22	2	4	4-18	228	-	160	-	13.2	-	
25	210	135	100	78	58	24	2	4	4-18	250	-	180	-	14	-	
32	230	150	110	82	66	24	2	4	4-23	326	-	220	-	15	-	
40	260	165	125	95	76	26	3	4	4-23	359	-	240	-	29	-	
50	300	195	145	112	88	28	3	4	4-25	414	710	280	DZW15	49	82	
65	340	220	170	138	110	32	3	4	8-25	434	750	320	DZW20I	65	104	
80	380	230	180	148	121	34	3	4	8-25	547	785	400	DZW30	95	138	
100	430	265	210	172	150	38	3	4.5	8-30	621	837	450	DZW45	115	243	
125	500	310	250	210	176	42	3	4.5	8-34	732	-	450	-	149	-	
150	550	350	290	250	204	46	3	4.5	12-34	840	-	500	-	310	-	
200	650	430	360	312	260	54	3	4.5	12-41	925	-	550	-	590	-	
J41 ^H _Y -160																
15	170	110	75	52	40	24	2	4	4-18	148	-	140	-	12.2	-	
20	190	130	90	65	51	26	2	4	4-23	156	-	160	-	15	-	
25	210	140	100	72	58	28	2	4	4-23	125	-	180	-	17	-	
32	230	165	115	85	66	30	2	4	4-25	200	-	200	-	21.4	-	
40	260	175	125	92	76	32	3	4	4-27	231	-	240	-	32	-	
50	300	215	165	132	88	36	3	4	8-25	262	-	250	-	52	-	
65	340	245	190	152	110	44	3	4	8-30	303	-	320	-	69	-	
80	380	260	205	168	121	46	3	4	8-30	341	-	400	-	98	-	
100	430	300	240	200	150	48	3	4.5	8-34	485	-	450	-	119	-	