



氟衬里截止阀

Teflon-lining Globe Valves Class300 Class400 W Js45Y、W Js545Y、W Js945Y



上慧阀门
www.shxvalve.com



执行标准 Administer Standard

设计规范 Design Spec	结构长度 Face to Face	连接法兰 Flange Dnd	试验与检验 Test & Check	产品标识 Marking	供货规范 Supply
GB/T 12233 (GB/T 12235)	GB/T 12221	JB/T 78; JB/ 79	GB/T13927	GB/T12220	JB/T 7928

性能规范 Property and Specification

衬里/阀座 Lining/seat	代号 Code	适用温度℃ Suitable Temperature℃	适用介质 Suitable medium
PTFE(F4)	F4	≤180	除熔融碱金属，元素氟外的各种浓度的酸、碱、盐、王水、有机酸等强腐蚀性介质。 All kinds of acid, alkali, salt, aquaregia, organic acid etc strong corrosive medium except molten alkali metals and element fluorine.
PCTFE(F3)	F3	≤120	
PFE(F46)	F46	≤150	
PFA(可溶性F4)	FA	≤180	
PVD(F2)	F2	≤100	
RPTFE(RF4)	FR4	≤180	

主要零部件材料 Main Part Material

零件名称 Part Name	铸钢 Cast steel	不锈钢/耐腐蚀钢 Stainless acid resistant cast steel		超低碳不锈钢/耐腐蚀钢 Super-low ~stainless acid resistant cast steel	
	C	P	R	PL	RL
阀体/阀盖 Body/Cover	WCB	CF8	CF8M	CF3	CF3M
阀瓣/阀杆 Disc/stem	2Cr13	1Cr18Ni19	1Cr18Ni12Mo2Ti	00Cr18Ni10	00Cr17Ni14Mo2
衬里/阀座 Lining/seat	PTFE(F4)、PCTFE(F3)、FEP(F46)、PFA(可溶性F4)				
填料压盖 Packing cocer	WCB	CF8	CF8M	CF3	CF3M
填料 Packing	PTFE(F4)	PTFE(F4)		PTFE(F4)	
活结螺栓 Eyelet bolt	35	1Cr17Ni2		1Cr17Ni2	
阀杆螺母 Stem nut	ZCuAl10Fe3	ZCuAl10Fe3		ZCuAl10Fe3	
紧锢螺栓 Clamp bolt	35	1Cr17Ni2		1Cr18Ni9Ti	
螺母 nut	45	0Cr18Ni9		0Cr18Ni9	
手轮 Hand wheel	WCB	WCB		WCB	